GRILS41

DDR2-667, PC2-5300, Registered, ECC, 1.8V, 240-pin, VLP DIMMs

Products in Family

GRILS41S/4GB (2 x 2GB 1R VLP DIMMs)
GRILS41-6/8GB (2 x 4GB 2R VLP DIMMs)

Features	Description
240-pin JEDEC-compliant DIMMs 133.35 mm wide by 18.3 mm high (.72" x 5.25") Data Transfer Rate: 5.3 Gigabytes/sec Operating Voltage: 1.8 V ±0.1 Error Checking and Correction (ECC) bits Supports Intel SDDC and Chipkill Advanced ECC Features Fully RoHS Compliant	Each GRILS41 upgrade consists of a matched pair of DDR2-533 Registered VLP DIMMs with address/command parity functionality. One 2K-bit EEPROM is used for Serial Presence Detect.

Dataram Product	IBM Microsystems Product	Supported in these IBM systems:
GRILS41S/4GB GRILS41-6/8GB	46C0512 46C0513	BladeCenter LS21 (7971), LS22 (7901), LS41 (7972), LS42 (7902)



Notes

Tolerances on all dimensions except where otherwise indicated are ±.13 (.005).

All dimensions are expressed in millimeters.



Detail A



Detail B

Copyright © 2009 Dataram Corporation | U.S.A. Headquarters +1 609-799-0071 | Offices in Europe and Asia | www.dataram.com

The information contained in this document has been carefully checked and is believed to be reliable and accurate. However, Dataram assumes no responsibility for errors.